



Parameters for Manual Traction Lift

Parameters for Automatic Traction Lift

Capacity		Lift Well		Cabin Inside		Entry
Person	Kgs.	(width) A	(depth) B	(width) C	(depth) D	E
5	340	1600	1400	1070*	900*	700
6	408	1650	1500	1120*	990*	700
8	544	1800	1650	1320*	1100*	800
10	680	1800	2050	1070	1650	800
13	884	1850	2500	1070	2100	800/900
15	1020	1900	2600	1120	2200	800/900
20	1360	2100	2800	1320	2400	900/1000
26	1786	2400	2800	1620	2400	900/1000

Capacity		Lift Well		Cabin Inside		Entry
Person	Kgs.	(width) A	(depth) B	(width) C	(depth) D	E
5	340	1600	1500	1120	850*	700
6	408	1650	1600	1220	880*	700
8	544	1850	1700	1120	1280*	800
10	680	2000	1850	1270	1380	800
13	884	2100	2600	1070	2100	800/900
15	1020	2100	3000	1070	2400	800/900
20	1360	2300	3000	1320	2400	900/1000
26	1786	2450	3000	1620	2400	900/1000

All Dimension are in mm | This is General Data, it may be changed without notice
 All hoist way wells should be minimum 230 brick 150 mm R.C.C.